



BK-ADB-03

**AdBlue / Diesel Exhaust Fluid
(1000 L)**

**-ISO 22241 | ISO 9001-2013 | DIN 70070 |
EC No 1907/2006 and 1272/2008
VDA Institute**

FEATURES:

AdBlue is a transparent liquid with weak alkaline (ph = 9~10). It is used to ensure optimal performance and reliability of SCR system. By injecting the fluid into a separate small tank, the fluid breaks down noxious gases into Nitrogen, Oxygen and water, minimising environmental impact.

Certifications:

-ISO 22241 | ISO 9001-2013 | DIN 70070 |
EC No 1907/2006 and 1272/2008 | VDA Institute



Parameter	Unit	Test Method	Results	Limits	
				Min	Max
Urea	% w/w	ISO 22241-2 Annex C	32.6	31.8	33.2
Density @ 20°C	g/cm ³	ISO 3675	1.0914	1.087	1.0930
RI @ 20°C	-	ISO 22241-2 Annex C	1.3833	1.3814	1.3843
Alkalinity as NH ₃	% w/w	ISO 22241-2 Annex D	< 0.2	-	0.2
Biuret	% w/w	ISO 22241-2 Annex E	0.27	-	0.3
Aldehyde	mg/kg	ISO 22241-2 Annex F	< 5.0	-	5.0
Insolubles	mg/kg	ISO 22241-2 Annex G	< 20	-	20
Phosphate (PO ₄)	mg/kg	ISO 22241-2 Annex H	9.9	-	0.5
Calcium	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.5
Iron	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.5
Copper	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.2
Zinc	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.2
Chromium	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.2
Nickel	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.2
Aluminium	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.5
Magnesium	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.5
Sodium	mg/kg	ISO 22241-2 Annex I	1.4	-	0.5
Potassium	mg/kg	ISO 22241-2 Annex I	< 0.1	-	0.5
Identity	-	ISO 22241-2 Annex J	Identical to Ref	Identical to Ref	

LEAD TIMES	AdBlue/ Diesel Exhaust Fluid
Packaging information	1000L per IBC
Payment	EFTPOS available on collection or 10% discount cash
MOQ	1 x 1000L IBC
Collection Address	ASPM Logistics 62 Belmore Rd North, Riverwood Sydney. Fork lift on site.

+61 425 236 248 (Scott Whittaker)

scott@bioklenz.com

www.bioklenz.com

